

# ENVIROBLEND<sup>®</sup>

## WITH SLIKSHOT



- MEETS OR EXCEEDS ALL REQUIREMENTS FOR WOOD AND PAPER FIBER MULCH
- COMBINATION OF 70% WOOD FIBER AND 30% CELLULOSE FIBER
- PROVIDES SUPERIOR EROSION CONTROL AND GERMINATION PERFORMANCE WHEN COMPARED TO 100% PAPER MULCH
- ENVIROBLEND COVERS 20% MORE PHYSICAL GROUND PER POUND THAN 100% PAPER MULCH, SAVING YOU TIME AND MONEY

### DIRECTIONS FOR USE

PLEASE REFER TO EQUIPMENT MANUFACTURER'S LOADING INSTRUCTIONS.



### PHYSICAL PROPERTIES

MOISTURE CONTENT	12% +-3
ORGANIC CONTENT	96.0% +-1
WOOD FIBER	70% MIN
PAPER FIBER	30% MAX
ASH CONTENT	1.0% +-1
pH RANGE	4.8 +-2
WATER HOLDING CAPACITY	1100% MIN

### TYPICAL APPLICATION RATE

MODEST TO 4:1 SLOPE	1500 LBS / ACRE
4 TO 1 SLOPE	2000 LBS / ACRE
3:1 TO 2:1 SLOPE	2500 LBS / ACRE

### PACKAGING

NET WEIGHT 50 LB BALE, 40 BALES PER PALLET



### DISTRIBUTED BY

